

# MECARING DW 110-250


**BOOST YOUR  
PRODUCTION AND  
RELEASE OPERATORS TO  
MORE VALUABLE WORK**

MECARING solutions are easily integrated to corrugated pipe extrusion. Mecaring DW makes automatic external seal inserting easy and effective for inline or offline use.

## MECARING DW 110-250

### FEATURES:

- For corrugated pipes OD from 110 to 250 mm
- Pipe lengths from 2 m
- For flexible rubber gaskets in several profiles
- Application speed up to 150 gaskets per hour
- High capacity gasket magazine, up to 360 gaskets
- Special designed tools for each gasket type and diameter
- Tool changing and machine setting time less than 15 minutes
- Controlled by Siemens PLC with touch screen
- Interface for extrusion line control system
- Flexible operating modes: pipe through machine or pipe in-out



### TECHNICAL SPECIFICATION:

- Overall machine dimensions: 2000 x 1700 x 2100 mm
- Pipe center heights 1000 mm (adjustable)
- Compressed air connection: Inlet 1/2", min operating pressure 6 bar
- Electrical connection 400/230 VAC, 16 A

### WATCH THE VIDEO

<https://www.youtube.com/watch?v=VfI36NTKOHQ>

### ASK LAYOUT DRAWING AND PRICING

[mikko.vuorinen@extron-mecanor.com](mailto:mikko.vuorinen@extron-mecanor.com)

## EXTRON ENGINEERING OY / MECANOR OY

Talittatie 4, FI-37800 Akaa, Finland  
tel. +358 40 172 7391  
[info@extron-mecanor.com](mailto:info@extron-mecanor.com)



[www.extron-mecanor.com](http://www.extron-mecanor.com)

